

DUTY GEAR WILL FIT CHART
PT 3 DG Duty and Tactical Holsters with Lights -Pistols



PT 3 Pistols w/ Light

Note: Items with an X by the gun description fit with or without a light

Gun Mfr/Model		BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
Beretta		BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
92F w/ SureFire MR-11 adapter & Surefire X200 or X300		4.90"	73421		73421													
Vertec 92FS, 96 w/ M3, M6, M3 LED IT Tactical Illuminator Light, Streamlight TLR-1, TLR-2, or Insight XTI Procyon		4.70"	73421		73421													
PX4 Storm 9mm & .40 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, M6, Insight XTI Procyon, TLR-1, TLR-1HL, TLR-2, Surefire X200, X300, X300U lights		4.00"	18021		18021													
APX 9/40 W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U light		4.25"				6732	6732	6732		6732	6732							
Caspian		BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
1911 w/Military mount M3X/M6X light		5.00"	5322															
1911 w/ Military Mount w/ Beamshot Light Model 8800		5.00"	5322															
Colt		BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
1911-A1 Non Rail, w/ Surefire mount MR07, w/Surefire X200, X300, or X300U		5.00"	530		530													
Govt. 1911 w/ Sure-Fire X200, X300, and X300U		5.00"	530		530													
Colt M45A1 COBP w/ Surefire X200, X300, or X300U		5.00"	530		530													
CZ		BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
P07 w/ ITI M3, TLR-1, Surefire X200 or X300		3.80"				2922	2922	2922		2922	2922							
P10C W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI Streamlight M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	X	4.02"				3922	3922	3922		3922	3922							
P10F W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI Streamlight M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	X	4.50"				4922	4922	4922		4922	4922							
FN		BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
Five-Seven w/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, Tactical Illuminator light refire M3, M6, M3 LED, Insight XTI Procyon or Streamlight TLR-1 and TLR-2 N/A for M3X/M6X. NOTE: Retention is reduced by removal of light		4.80"	6121		6121													
FNS .40 w/ M3, TLR-1, Surefire X200, X300		4.00"				2662	2662	2662		2662	2662							
FNS 9 w/ M3, TLR-1, Surefire X200, X300, or X300U light		4.00"				2692	2692	2692		2692	2692							
FNS 40 w/ M3, TLR-1, Surefire X200, X300 Light		5.00"				2672	2672	2672		2672	2672							
FN 509 W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI Streamlight M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	X	4.00"				2702	2702	2702		2702	2702							
Glock		BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
17, 22 Gen1-4 w/ Surefire X200, X300, or X300U		4.50"	836		836													
17, 22 All Gen W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI Streamlight M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	X	4.50"				8325	8325	8325		8325	8325	8325	8325	8325	8325	8325	8325	8325
17, 22 All Gen W/ Streamlight TLR-7, Surefire XC-1, XC-2, Nightstick TCM 550XL, or Inforce APLc		4.50"										8327	8327	8327	8327	8327	8327	8327
17, 22 All Gen W/ Surefire X300, or X300U with Pressure Switch NOTE: Retention is reduced by removal of light		4.50"				8301	8301	8301		8301	8301							
17, 22 All Gen W/ ITI Streamlight M3, TLR-1, TLR-1HL with Pressure Switch NOTE: Retention is reduced by removal of light		4.50"										8302	8302	8302	8302	8302	8302	8302
17, 22 with SureFire All Gen 200, X300, X300U, X300V, X400, X400U, or X400V Light		4.50"					8314				8314							
17, 22, 31 All Gen W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, M3X, M6, M6X, Streamlight TLR-1, TLR-1HL, TLR-2 or TLR-2HL NOTE: Retention is reduced by removal of light		4.50"	8321		8321	8321	8321	8321		8321	8321							
17, 22 All Gen with DBAL light		4.50"	8317		8317													
17, 22 All Gen with SBAL light		4.50"				8323	8323	8323		8323	8323							
17, 22 All Gen with SureFire X400 Light		4.50"		8314														
17, 22 Gen1-4 Dual Magazine Release with ITI M3		4.50"	9832		9832													
17, 22 Gen1-4 Dual Magazine Release with Glock GTL10 Light		4.50"	98310		98310													

DUTY GEAR WILL FIT CHART
PT 3 DG Duty and Tactical Holsters with Lights -Pistols

Gun Mnfctr./Model	BBL.	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
17, 22 Gen1-4 Dual Magazine Release with Glock GTL 10 Light, or GTL 21, GTL 22 Light/Laser Combo	4.50"	98310		98310													
17, 22, 31 Gen1-4 w/ITI Streamlight TLR-1, TLR-1HL, M3 or Insight XTI Procyon NOTE: Retention is reduced by removal of light	4.50"	832		832													
17, 22, 31 All Gen w/ Glock Tactical Light Systems: GTL 10 (light only), GTL21, GTL22 (light laser combo), GTL51 (light/laser combination), GTL52 (light/laser with dim-switch) Note: holster will not retain weapon without light attached	4.50"	8310		8310	8310	8310	8310		8310	8310							
17, 22, 31 Gen1-4 with Beamshot Model 8000 or Model 8100	4.50"	8312		8312													
17, 22, 31 Gen1-4 w/Insight Technology Streamlight M3X / M6X	4.50"	8312		8312													
17, 22, 31 Gen1-4 w/ SureFire P111, P111C or P111D with trigger guard rail mount NOTE: Retention is reduced by removal of light	X 4.50"	830		830													
17, 22, 19 and 23 Gen1-4 with SureFire, X200, X300, X300U, X300V, X400, X400U, or X400V Light	4.50"	8314	8314	8314													
19, 23, 19X, 45 All Gen W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI Streamlight M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	X 4.00"	2832		2832	28325	28325	28325	2832	28325	28325	28325	28325	28325	28325	28325	28325	28325
19, 23, 19X 45 All Gen W/ Streamlight TLR-7, Surefire XC-1, XC-2, Nightstick TCM 550XL, or Inforce APLc	4.00"									28327	28327	28327	28327	28327	28327	28327	28327
19, 19X, 23, 45 All Gen with SureFire, X200, X300, X300U, X300V, X400, X400U, or X400V Light	4.00"					28314				28314							
19, 23, 19X, 45 All Gen W/ Surefire X300, or X300U with Pressure Switch NOTE: Retention is reduced by removal of light	4.00"				28301	28301	28301		28301	28301							
19, 19C, 23, 23C Gen1-4 w/ Surefire X200 or X300	4.00"	2830		2830													
19, 19C, 23, 23C, 25, 32, 32C Gen1-4 with ITI Streamlight M3, TLR-1 or Insight XTI Procyon NOTE: Retention is reduced by removal of light	X 4.00"	2832		2832													
19, 23 Gen1-4 W/ ITI M3, M3X, M6, M6X, Streamlight TLR-1, TLR-1HL, TLR-2 or TLR-2HL NOTE: Retention is reduced by removal of light	4.00"	8321		8321	28321	28321	28321		28321	28321							
19, 23 Gen1-4 w/ Glock Tactical Light Systems: GTL 10 (light only) Note: N/A: for Glock light system GTL21, GTL22 (light laser combo) NOTE: Retention is reduced by removal of light	4.00"				28310	28310	28310		28310	28310							
20, 21, 21SF, 29, or 37 Gen1-4 w/ STD Glock Rails with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	X 4.60"				3832	3832	3832		3832	3832	3832	3832	3832	3832	3832	3832	3832
20, 21 Gen1-4 W/ Streamlight TLR-7, Surefire XC-1, XC-2, Nightstick TCM 550XL, or Inforce APLc	4.60"									38327	38327	38327	38327	38327	38327	38327	38327
20, 21, 21SF Gen1-4 with ITI Streamlight TLR-1, M3 light or Insight XTI Procyon NOTE: Retention is reduced by removal of light	X 4.50"	3832		3832													
20, 21 Gen1-4 w/ STD Glock Rails with Inforce APL, Surefire X200 or X300 light NOTE: Retention is reduced by removal of light	4.60"	3830		3830													
21SF Gen1-4 w/STD Glock Rails with Surefire X200 light or X300 NOTE: Retention is reduced by removal of light	4.60"	3830		3830													
20, 20C, 21, 21C Gen1-4 w/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, Insight TLR-1, TLR-2, Technology M3, M6, M3 LED, or Insight XTI Procyon NOTE: Retention is reduced by removal of light	4.60"	38321		38321													
20, 21 Gen1-4 w/STD Glock Rails w/Laser/Tac 2 (6v) from Laser Device Inc. Or Streamlight TLR-1 and TLR-2	4.50"	38321		38321													
21SF Gen1-4 w/STD Glock Rails w/Laser Device Inc, Laser-Tac 2 (6V) Or Streamlight TLR-1	4.60"	38321		38321													
21SF Gen1-4 w/STD Glock Rails with Streamlight M3, M6, M3 LED, or Insight XTI Procyon. NOTE: Retention is reduced by removal of light	4.60"	38321		38321													
Glock 20 & 21SF Gen1-4 with Dual Magazine Release with ITI M3, M6, TLR-1, TLR-2, Surefire X200, X300, X300U, Insight XTI Procyon	4.60"	938321		938321													
29, 30 All Gen W/ Streamlight TLR-7, Surefire XC-1, XC-2, Nightstick TCM 550XL, or Inforce APLc	3.78"									48327	48327	48327	48327	48327	48327	48327	48327
34 All Gen with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	5.32"	6832		6832	68325	68325	68325		68325	68325	68325	68325	68325	68325	68325	68325	68325

DUTY GEAR WILL FIT CHART
PT 3 DG Duty and Tactical Holsters with Lights -Pistols

Gun Mnfctr./Model		BBL.	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
34, 35 Gen1-4 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	X	5.32"				6832	6832	6832		6832	6832							
34, 35 Gen1-4 w/ITI Streamlight M3 or Insight XTI Procyon NOTE: Retention is reduced by removal of light	X	5.32"	6832		6832													
34, 35 Gen1-4 w/ IT Tactical Illuminator Light M3, M6, M3 LED, TLR-1, TLR-2, or Insight XTI Procyon Note: N/A for M3X/M6X. NOTE: Retention is reduced by removal of light.		5.32"	68321		68321													
37 Gen1-4 with ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U, or Insight XTI Procyon	X	4.50"				7832	7832	7832		7832	7832							
37 Gen1-4 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200 or X300		4.50"	7832		7832													
41 Gen4 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U lights	X	5.31"				8932	8932	8932		8932	8932							
47 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U lights	X	4.50"				8972	8972	8972		8972	8972	8972	8972	8972	8972	8972	8972	8972
Heckler & Koch			6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
USP 9, 40 w/ H&K Light (UTL)		4.25"	932		932													
USP 9, 40 Hammer Down or Cocked and locked w/ B & T Adapter and IT Tactical light M3, M6, M3 LED, or Insight XTI Procyon. NOTE: Retention is reduced by removal of light		4.25"	9221		9221													
USP 9, 40 D.A.O. w/Surefire mount w/ Insight Technology M3X or M6X light or ITI SSL-1. NOTE: Retention is reduced by removal of light.		4.25"	19312		19312													
USP 9, USP .40 with Spurred Hammer and Surefire Mount MR09, and Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, M6, TLR-1, TLR-2, Surefire X200, X300, X300U or Insight XTI Procyon lights		4.13"	9321		9321													
USP 40C with GG&G Slime Rail Adapter and Insight Technology M3, M6, M3X LED Tactical Illuminator Light, ITI SSL-1, or Insight XTI Procyon. Bobbed Hammer Only Note: N/A for M6X NOTE: Retention is reduced by removal of light		3.58"	29111		29111													
USP 9C and .40C with TLR-3		3.58"				29116	29116	29116		29116	29116							
H&K 45 Compact with TLR-3		3.94"	49316		49316													
USP 45 LEM (D.A.O. (Bobbed Hammer)) w/Surefire X200 light adapter with Surefire X200 or X300 light NOTE: Retention is reduced by removal of light		4.41"	1930		1930													
USP 45 LEM (D.A.O. (Bobbed Hammer)), USP 45 Spurred Hammer w/Surefire X200 light adapter with Surefire X200 or X300 light NOTE: Retention is reduced by removal of light		4.41"	930		930													
USP 45 w/ H&K Light (UTL)		4.41"	932		932													
USP 45 w/ H&K USP Light Cocked & Locked Only		4.41"	922															
USP .45 with Spurred Hammer and Surefire Mount MR09, Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, M6, TLR-1, TLR-1HL, TLR-2, Surefire X200, X300, or Insight XTI Procyon light		4.41"	9321		9321													
P2000 (U.S. Version) w/ ITI M3/M6 or Insight XTI Procyon Light.		3.5"	19721		19721													
P2000 (US Version) DAO, Bobbed Hammer, w/Insight Technology M3X Light Only		3.66"	9711		9711													
P2000 DAO (bobbed Hammer) with B&T adaptor and a Glock Light System: Models: GTL 10 (light only), GTL21 (light/laser combination), GTL22 (light/laser combination), GTL51 (light/laser combination), GTL52 (light /laser with dim-switch)		3.50"	9710		9710													
P2000 European Version with B & T adapter (TL P2000) with M3/M6 IT tactical illuminator light, ITI SSL-1, or Insight XTI Procyon NOTE: Retention is reduced by removal of light.		3.50"	9721		9721													
P2000 US Version with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U lights	X	3.50"				1972	1972	1972		1972	1972							
H&K P30 with ITI M3, TLR-1, Surefire X200, or X300		3.85"	2952		2952													
H&K P30 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U		3.85"				2952	2952	2952		2952	2952							
H&K P30 with ITI M3, TLR-2		3.85"	29521		29521													
H&K P30 with DBAL light		3.85"	29517		29517													
H&K P30L with DBAL Light		4.45"	39517		39517													

DUTY GEAR WILL FIT CHART
PT 3 DG Duty and Tactical Holsters with Lights -Pistols

Revised: 3/13/20

Gun Mnfctr./Model	BBL.	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
H&K P30L with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	4.45"	3952		3952	3952	3952	3952			3952							
HK 45 Cocked & Locked with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, TLR-1, TLR-1HL, Surefire X200, X300, X300U, LAS-TAC2, or SSL-1	4.53"	3930		3930													
VP9 with TLR-2	4.09"	59321		59321													
VP9 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	4.09"				5932	5932	5932		5932	5932							
VP9 with XC-1	4.09"				59322	59322	59322		59322	59322							
Kimber	BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
1911 w/ rails: Gold Combat RL; Custom TLE/RL w/Inforce APL, Surefire X200, X300, X300U light NOTE: Retention is reduced by removal of light	5.00"	5340		5340	560	560	560		560								
1911 w/ rails: Gold Combat RL; Custom TLE/RL w/ Surefire X200, X300, or X300U light NOTE: Retention is reduced by removal of light	5.00"	5340		5340													
Gold Combat RL II Warrior w/light rail w/Streamlight M3, M6, M3 LED, or Insight XTI Procyon	5.00"	5621		5621													
Sphinx	BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
SDP-S With WLI-AA With laser	4.50"				28115	28115	28115			28115							
SDP Compact With WLI-AA With laser	4.50"	28215		28215													
Sig Sauer	BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
P220R W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI Streamlight M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	4.411"	27721		27721							7702	7702	7702	7702	7702	7702	7702
P226R W/ITI Streamlight M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	4.41"										4772	4772	4772	4772	4772	4772	4772
Sig P220R DAK, P226R DAK with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, M6 light, ITI SSL-1, Streamlight TLR-1, TLR-2, or Insight XTI Procyon. NOTE: Retention is reduced by removal of light	4.41"	27721		27721													
P220R, P226R DASA/ DAK W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U, or Insight XTI Procyon NOTE: Retention is reduced by removal of light	X 4.41"				7742	7742	7742		7742	7742							
P226 (full size hammer) with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, Insight Technology Mount (ITI), Streamlight Tactical Illuminator Light Model M3, M6, M3 LED, Streamlight TLR-1, TLR-2, TLR-2HL, or Insight XTI Procyon. NOTE: Retention is reduced by removal of light	4.41"	7721		7721													
P220R, P220S, P226S, P226SO, P226R w/Accy Rails (DASA Spurred Hammer) w/M3, M6 Light, Streamlight TLR-1, TLR-2, or Insight XTI Procyon.	4.41"	77421		77421													
P220R, P226R (DA/SA Spurred Hammer) w/ Insight Technology Streamlight M3X or M6X Light or Surefire X400 light NOTE: Retention is reduced by removal of light	4.41"	77412		77412													
P220, P220ST, P220R, P226R (DA/SA Spurred Hammer) w/ Sure Fire X200 or X300 Light NOTE: Retention is reduced by removal of light	4.41"	7740		7740													
P220, P226 with Beamshot Model 8000 or Model 8100	4.41"	7712		7712													
P220, P226 with IT Mount and Insight Technology M3X, M6X. NOTE: Retention is reduced by removal of light	4.41"	7712		7712													
P220, P226 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI Mount M3X, M6X, M3, M6, TLR-1, TLR-2, SureFire X200 or X300	X 4.41"	7712		7712													
P220R, P226R with SureFire X400 or X400U	4.41"	77414		77414													
P226 E2 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, TLR-1, TLR-1HL, X200, X300, or X300U	4.41"				7742	7742	7742		7742	7742							
P226 MK25 with X300 or X300 Ultra light	X 4.41"	7740		7740													
P226R X-Five with Surefire X200, X300, or X300U Light	5.00"	3770		3770													
P227 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Inforce APL, Surefire X200, X300, X300U or Insight XTI Procyon (Note: Holster MFR after 29NOV13, however older models will fit but the SLS hood rubs against the weapon's hammer)	4.40"						7742			7742							

DUTY GEAR WILL FIT CHART
PT 3 DG Duty and Tactical Holsters with Lights -Pistols

Gun Mfctr./Model	BBL.	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
P227 W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI Streamlight M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	4.40"										6772	6772	6772	6772	6772	6772	6772
P228,P229 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, M3, M6, M3 LED light with ITI mount, Streamlight TLR-1, TLR-2 or Insight XTI Procyon.	3.9"	7421		7421													
P229R DASA (Spurred Hammer) with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, M3, M6 or M3 LED light, Streamlight TLR-1, TLR-2, or Insight XTI Procyon. NOTE: Retention is reduced by removal of light/A M3X, M6X.	3.9"	74421		74421													
P229R DAK with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, IT Tactical Illuminator Light M3, M6, M3 LED, Streamlight TLR-1, TLR-2, or Insight XTI Procyon. NOTE: Retention is reduced by removal of light	3.9"	17421		17421													
P229R DAK w/ Insight Technology M3X or M6X light. NOTE: Retention is reduced by removal of light	3.9"	17412		17412													
P229R DASA w/Spurred Hammer w/Surefire X200 or X300 Light NOTE: Retention is reduced by removal of light.	3.9"	7440		7440													
P229R with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HLSurefire X200, X300, or X300U lights	3.9"				7442	7442	7442		7442	7442							
P229 w/ ITI mount and ITI M3X light	3.9"	7411		7411													
P229R .40 S&W W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI Streamlight M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	3.90"										4472	4472	4472	4472	4472	4472	4472
P229R 9mm W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI Streamlight M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	3.90"										4742	4742	4742	4742	4742	4742	4742
P250 9/40 or M17 with ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	4.70"				4502	4502	4502		4502	4502	4502	4502	4502	4502	4502	4502	4502
P250 Compact and Carry 9mm and .40 S&W or M18 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	3.90"				7502	7502	7502		7502	7502	7502	7502	7502	7502	7502	7502	7502
P250 .45 ACP with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	3.90"										4512	4512	4512	4512	4512	4512	4512
P250 Compact and Carry .45 ACP with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	3.90"										7512	7512	7512	7512	7512	7512	7512
P320 9/40 or M17 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	4.70"			4502	4502	4502	4502		4502	4502	4502	4502	4502	4502	4502	4502	4502
P320 X-Full, X-Vtac, or M17 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	4.70"										4502	4502	4502	4502	4502	4502	4502
P320 9/40, X-Full, X-Vtac, or M17 W/ Streamlight TLR-7, Surefire XC-1, XC-2, Nightstick TCM 550XL, or Inforce APLc	4.70"										45027	45027	45027	45027	45027	45027	45027
P320 Compact and Carry 9mm and .40 S&W or M18 with ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	3.90"				7502	7502	7502		7502	7502	7502	7502	7502	7502	7502	7502	7502
P320 Compact and Carry 9mm and .40 S&W or M18 W/ Streamlight TLR-7, Surefire XC-1, XC-2, Nightstick TCM 550XL, or Inforce APLc	3.90"										75027	75027	75027	75027	75027	75027	75027
P320 .45 ACP with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	4.7"										4512	4512	4512	4512	4512	4512	4512
P320 Compact and Carry .45 ACP with ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	3.90"										7512	7512	7512	7512	7512	7512	7512
P320 X-Carry with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	3.90"										7522	7522	7522	7522	7522	7522	7522
Sig Pro SPC 2009 w/Sig metal rail adaptor and IT Streamlight M3 tactical illuminator light or Insight XTI Procyon NOTE: Retention is reduced by removal of light	3.5"	2782		2782													
1911 GSR w/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, M6, Streamlight TLR-1, TLR-1HL, TLR-2, Surefire X200, X300, X300U, SSL-1, or Insight XTI Procyon NOTE: Retention is reduced by removal of light	5.00"	25621		25621													

DUTY GEAR WILL FIT CHART
PT 3 DG Duty and Tactical Holsters with Lights -Pistols

Gun Mnfctr./Model	BBL.	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
Sig Pro P2022 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, Insight Technology M3, M6, M3 LED Tactical Illuminator light, ITI SSL-1, Streamlight TLR-1, TLR-2, or Insight XTI Procyon. NOTE: Retention is reduced by removal of light	3.50"	27821		27821													
Smith & Wesson	BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
M&P 2.0 9C with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	4.00"				2222	2222	2222		2222	2222	2192	2192	2222	2222	2222	2222	2222
M&P 2.0 40C with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	4.00"				2192	2192	2192		2192	2192	2192	2192	2192	2192	2192	2192	2192
M&P 2.0 9 & 40 W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, M6 Streamlight TRL-1, TLR-1HL, or TRL-2	4.25"	21921		21921													
M&P 2.0 9 & 40 W/ Surefire X200, X300, or X300U	4.25"	2190		2190													
M&P 2.0 9 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	4.25"				2222	2222	2222		2222	2222	2192	2192	2222	2222	2222	2222	2222
M&P 2.0 40 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	4.25"				2192	2192	2192		2192	2192	2192	2192	2192	2192	2192	2192	2192
M&P 2.0 9L with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	5.00"				8182	8182	8182		8182	8182	8192	8192	8182	8182	8182	8182	8182
M&P 2.0 40L with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	5.00"										8192	8192	8192	8192	8192	8192	8192
M&P 2.0 45 without manual safeties with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	4.60"				4192	4192	4192		4192	4192	4192	4192	4192	4192	4192	4192	4192
M&P 1.0 9 & 40 W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, M6 Streamlight TRL-1, TLR-1HL, TRL-2, Insight XTI Procyon, or Surefire X200, X300	4.25"	21921		21921													
M&P 1.0 9 & 40 with SureFire X200 or X300 lights	4.25"	2190		2190													
M&P 1.0 9 & 40 with XC-1	4.25"										21922	21922	21922	21922	21922	21922	21922
M&P 1.0 9 & 40 with SureFire X400 Ultra light	4.25"	21914		21914													
M&P 1.0 9 & 40 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	X 4.25"				2192	2192	2192		2192	2192	2192	2192	2192	2192	2192	2192	2192
M&P 1.0 9L & 9 Pro with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	X 5.00"										8192	8192	8192	8192	8192	8192	8192
M&P 1.0 45C without manual safeties W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, TLR-1, TLR-1HL, SureFire X200, X300, or X300U	4.00"				9192	9192	9192		9192	9192							
M&P 1.0 45C with manual safeties W/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, TLR-1, TLR-1HL, SureFire X200, X300, or X300U	4.00"				9202	9202	9202		9202	9202							
M&P 1.0 45 without manual safeties with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	4.60"				4192	4192	4192		4192	4192	4192	4192	4192	4192	4192	4192	4192
M&P 1.0 45 with or without manual safeties with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U lights	4.60"	51921		51921	5192	5192	5192		5192		4192	4192	4192	4192	4192	4192	4192
Sphinx	BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
SDP Standard w/ WL1-AA	4.5"								28115	28115							
SDP Standard w/ X400U	4.50"	28114		28114													
Springfield Armory	BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
1911 Operator w/Laser/Tac 2 (6v) from Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, Laser Device Inc. Or Streamlight TLR-1 and TLR-2.	5.00"	5621		5621													
1911 Operator w/ Inforce APL, Surefire X200, X300, or X300U light NOTE: Retention is reduced by removal of light	5.00"	5340		5340	560	560	560		560	560							
1911-A1 Non Rail, w/Surefire mount MR07, w/Surefire X200 or X300 Light	5.00"	530		530													
1911 Operator w/ M3, M6, M3 LED StreamLight, or Insight XTI Procyon	5.00"	5621		5621													
1911 Operator w/ M6X or M3X StreamLight or ITI SSL-1	5.00"	5612		5612													
1911 Operator with SureFire X200, X300, or X400 light	5.00"		5614														

DUTY GEAR WILL FIT CHART
PT 3 DG Duty and Tactical Holsters with Lights -Pistols

Gun Mnfctr./Model	BBL.	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
XD 9mm, .40, .45 w/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, M6, TLR-1, TLR-1HL, TLR-2, Surefire X200, X300, or Insight XTI Procyon NOTE: Retention is reduced by removal of light	4.00"	14821		14821													
XD .40, .45 w/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U, or Insight XTI Procyon NOTE: Retention is reduced by removal of light	4.00"				1482	1482	1482										
XD 9mm w/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U or Insight XTI Procyon NOTE: Retention is reduced by removal of light	4.00"				462	462	462										
XD 9mm, .40, .45 w/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, M6, TLR-1, TLR-1HL, TLR-2, Surefire X200, X300, X300U or Insight XTI Procyon NOTE: Retention is reduced by removal of light	5.00"	14921		14921													
XD 9mm, .40, w/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U, or Insight XTI Procyon	5.00"				1492	1492	1492										
XD MOD2 9mm, .40, w/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U, or Insight XTI Procyon	5.00"	14921		14921		1492	1492										
XD MOD2 9, .40 w/ITI M3, M6, TLR-1, TLR-1HL, TLR-2, Surefire X200, X300, or Insight XTI Procyon NOTE: Retention is reduced by removal of light	4.00"	14821		14821													
XD(M) .40 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, or X300U	4.00"				1462	1462			1462	1462							
XD(M) 9mm with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U, or Insight XTI Procyon NOTE: Retention is reduced by removal of light	4.50"				1452	1452	1452										
XD(M) .40 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U or Insight XTI Procyon NOTE: Retention is reduced by removal of light	4.50"				1462	1462	1462										
XD(M) 9mm & .40 with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, M6, TLR-1, TLR-1HL, TLR-2, Surefire X200, X300, or Insight XTI Procyon NOTE: Retention is reduced by removal of light	4.50"	14921		14921													
XD(M) .45 with ITI M3, M6, TLR-1, TLR-1HL, Surefire X200, X300, X300U or Insight XTI Procyon NOTE: Retention is reduced by removal of light	4.50"	14921		14921	1462	1462	1462		1462	1462							
STI/SVI	BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
1911 w/rails: STI 2011 Tactical 5, 2011 Tactical Lite 5, 1911 Duty One w/Surefire X200 or X300 light NOTE: Retention is reduced by removal of light	5.00"	5340		5340													
STI 2011 Tactical 5 w/ Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, M3, M6, M3 LED StreamLight, TLR-1, TLR-1HL, TLR-2, or Insight XTI Procyon	5.00"	5621		5621													
Walther	BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
P99Q/PPQ M1 and M2 9mm only (2008 & newer) with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U or Insight XTI Procyon lights	4.00"	3842		3842	3842	3842	3842		3842	3842							
P99Q/PPQ M1 and M2 (2008 & newer) with Inforce APL, Nightstick TWM-350, TWM-350S, TWM-850, TWM-850S, ITI M3, TLR-1, TLR-1HL, Surefire X200, X300, X300U or Insight XTI Procyon lights	5.00"				3852	3852	3852		3852	3852							
Wilson	BBL	6004/6005	6004USN	6280/6285/ 6282	6304/6305	6354/6355	6360/6365/ 6362	6378USN	6384/6385	6390/6395/ 6392	7004/7005	7280/7285/ 7282	7304/7305	7354/7355	7360/7365/ 7362	7384/7385	7390/7395/ 7392
1911 w/rails: CQB w/ Inforce APL, Surefire X200, X300, or X300U light NOTE: Retention is reduced by removal of light	5.00"	5340		5340	560	560	560		560	560							
1911 CQB w/light rail with M3/M6, or Insight XTI Procyon light	5.00"	5621		5621													

Although Safariland has attempted to provide accurate information regarding which specific holster models were designed to accommodate specifically identified handguns, human error such as typographical mistakes can and do occur. Therefore, Safariland disclaims any responsibility or liability for, or the consequences resulting from, such errors and urges user of this information to personally check for holster/handgun compatibility using the actual product.